

The Chemical Company

### Description

Pozzolith 200 N ready-to-use, liquid admixture is used for making more uniform and predictable quality concrete. It meets ASTM C 494/C 494M requirements for Type A, water-reducing, Type B, retarding, and Type D, water-reducing and retarding, admixtures.

# **Applications**

Recommended for use in:

- Prestressed concrete
- Precast concrete
- Reinforced concrete
- Shotcrete
- Lightweight concrete
- Pumped concrete
- 4x4™ Concrete
- Pervious Concrete
- Rheodynamic<sup>®</sup> Self-Consolidating Concrete (SCC)

# POZZOLITH® 200 N

# Water-Reducing Admixture

#### **Features**

- Reduced water content required for a given workability
- Controlled setting characteristics normal or retarded

#### **Benefits**

- Improved workability
- Reduced segregation
- Improved finishing characteristics for flatwork and cast surfaces
- Increased compressive and flexural strength

#### **Guidelines for Use**

**Dosage:** Pozzolith 200 N admixture is recommended for use at a dosage of 3-4 fl oz/cwt (195-260 mL/100 kg) of cementitious materials for Type A applications and up to 6 fl oz/cwt (390 mL/100 kg) for Type B and D requirements. Because of variations in job conditions and concrete materials, dosages other than the recommended amounts may be required. In such cases, contact your local BASF Construction Chemicals representative.

## **Product Notes**

Corrosivity – Non-Chloride, Non-Corrosive: Pozzolith 200 N admixture will neither initiate nor promote corrosion of reinforcing steel in concrete. This admixture does not contain intentionally-added calcium chloride or other chloride-based ingredients.

**Compatibility:** Pozzolith 200 N admixture may be used in combination with any BASF Construction Chemicals admixtures. When used in conjunction with other admixtures, each admixture must be dispensed separately into the mix.

# Storage and Handling

**Storage Temperature:** If Pozzolith 200 N admixture freezes, thaw at 35 °F (2 °C) or above and completely reconstitute by mild mechanical agitation. **Do not use pressurized air for agitation.** 

**Shelf Life:** Pozzolith 200 N admixture has a minimum shelf life of 18 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your BASF Construction Chemicals representative regarding suitability for use and dosage recommendations if the shelf life of Pozzolith 200 N admixture has been exceeded.

