

CANTILEVER SOLDIER BEAM WALL

Beams 11 through 19

Active soil pressure 55H (triangular distribution). Surcharge pressure 6H (rectangular), full height. Allowable passive resistance 375D. Maximum "excavation height" (for design) 8 feet. Caissons drilled in rock. 1982 UBC 2907(f)1 (unconstrained).

PARAMETER	UNITS	55H & 6s
=====		

BEAM DESIGN

UNIT ACTIVE PRESSURE	PCF	55
UNIT SURCH PRESSURE	PCF	6
EXCAVATION HEIGHT-H	FEET	8.00
SURCH HEIGHT-Hs	FEET	8.00
CENTROID HEIGHT-Ya	FEET	2.67
CENTROID HEIGHT-Ys	FEET	4.00
ACTIVE SOIL PRESS-Pa	PSF	1760
SURCHARGE PRESSURE-Ps	PSF	384
PRESSURE/FT F=Pa+Ps	PSF/FT	2144
CAISSON SPACING-X	FEET	8.00
CAISSON PRESSURE-F	LBS	17152
MOMENT-Mc	FT-LBS	49835
ALLOWABLE STRESS-Fb	LB/IN-2	23760
REQ'D SECTION MODULUS-Sc	IN-3	25.17
S	IN-3	29.0
I	IN-4	199
DEFLECTION	INCH	0.239

W12x16=17.1	IN-3	W14x22=29.0*	W18x35=57.6
W12x19=21.3		W14x26=35.3	W18x40=68.4
W12x22=25.4		W14x30=42.0	W18x46=78.8
W12x26=33.4		W14x34=48.6	W18x50=88.9
W12x30=47.2		W14x38=54.6	W18x55=98.3
W12x35=45.6		W14x38=54.6	W16x50=81.0

CAISSON DESIGN

FACTOR	NONE	2.34
LATERAL FORCE F	LBS	17152
DISTANCE M/F=Hr	FEET	2.91
ALLOW LATERAL BRG	LBS/SF/FT-DEPTH	375
CAISSON DIAMETER	FEET	2.00
DEPTH D (estimate)	FEET	10.89
CAISSON SHAPE FACTOR	NONE	1.75
UBC "S1"	NONE	1361.25
UBC "A"	NONE	8.42
DEPTH D	FEET	10.88

Result: Use W14x22 soldier beams 18'-0" long, embed 11'-0" in 24" in 24" caissons (structural concrete), spaced at 8'-0". Lean concrete to grade. 3x pressure treated wood lagging between beams, against front flanges, above caissons. All steel components to be double corrosion protected. Concrete wall 8' high w/1' freeboard above top of steel.

OWNERSHIP OF DOCUMENTS

These drawings and calculations, and the ideas and designs incorporated therein, as instruments of professional service, are the property of LAWRENCE B. KARP and are not to be used, in whole or part, for any other project without the express written authority of LAWRENCE B. KARP.