



NOTES

1. ROOF TILE FIELD SHALL BE AMERICAN SPANISH (ONE PIECE), AS MANUFACTURED BY CRAWCROFT BRICK CO. OF FRESNO PHONE 268-5635, OF SIZE, TYPE, AND NATURAL VARIEGATED RED COLORS, WITH SPACING AND EXPOSURE TO MATCH AND BLEND INTO EXISTING ROOF. WHERE SALVAGED TILE IS TO BE USED, IT SHOULD BE RANDOMLY PLACED AMONGST THE NEW TILE TO ACHIEVE A BLENDED APPEARANCE. APPROPRIATE TILE TRIM SHALL BE USED AS REQUIRED. WOOD RIDGE AND HIP STRINGERS AND WOOD TILE COVER COVER STRIPS SHALL BE INSTALLED ACCORDING TO CRAFT PRACTICE. TILE SHALL BE UNDERLAIN WITH 30# OR HEAVIER IMPREGNATED ROOFING FELT ON SHEATHING. FASTENINGS SHALL BE NON-CORROSIVE, OF LENGTHS TO GIVE PROPER PENETRATION. NATURAL GRAY CEMENT MORTAR LAP POINTING SHALL BE USED ACCORDING TO CRAFT PRACTICE. ALL MATERIALS SUBJECT TO OWNERS APPROVAL.
2. GUTTERS, DOWNSPOUTS, FLASHING, AND VALLEY METAL TO BE 16 OZ COPPER SHEET
3. EXISTING ROOFS SHALL HAVE TILE REMOVED, SUBROOF RENOVATED WHERE NECESSARY, AND AFTER DISCARDING BROKEN TILE, SALVAGED AND NEW TILE SHALL BE INSTALLED ON 30# OR HEAVIER IMPREGNATED ROOFING FELT AND NEW VALLEYS, FLASHINGS, AND GUTTER LEADS WITH NEW FASTENINGS, THROUGHOUT.